



SIZE	d	L	FLANGED								H	E	F	T	WEIGHT	
			D	C	g	f	t	N	h	kg					Q'ty	
15	1/2	15	131	95	70	51	1	12	4	15	73	40	50	6	2.6	
20	3/4	20	131	100	75	56	1	14	4	15	73	40	50	6	3.0	
25	1	25	151	125	90	67	1	14	4	19	89	50	65	8	4.7	
40	1 1/2	40	171	140	105	81	2	16	4	19	117	65	80	10	6.2	
50	2	50	201	155	120	96	2	16	4	19	136	80	95	12	8.0	

※ IN-SIDE
P. F. A. COATING (COLOR: GRAY)
THICKNESS: min 300 μm

No	NAME OF PART	MATERIAL	Q.T.Y	REMARKS
6	GASKET	T#9007-G20	4	
5	WASHER	SUS304	8	
4	BOLT	SUS304	8	
3	GLASS	TEMPERED GLASS	2	
2	COVER	SCS13A	2	
1	BODY	SCS13A	1	

※

No	NAME OF PART	MATERIAL	Q.T.Y	REMARKS
----	--------------	----------	-------	---------

NAME 10K CLEAR TYPE
FLANGED SIGHT GLASS

FLUID	TEST PRESSURE	TEST PRESSURE	BODY	
			(HYD)	1.5 MPaG
DESIGN PRESSURE	1.0 MPaG	TEST PRESSURE	SEAT	
			(HYD)	— MPaG
DESIGN TEMPERATURE	120 °C	TEST PRESSURE	(AIR)	
			(HYD)	— MPaG
			(AIR)	
			— MPaG	

DRAWING No _____ MODEL No 10FGTCL-13A

DATE	A. P	C. K	D. S	D. W
APR. 20, 2023	TAKAHASHI	TAKAHASHI	MORITA	HORIE



THREE-M INDUSTRY CO., LTD.

No	DESCRIPTION	DATE	A. P	C. K	D. W
REVISIONS					